

M/A-COM Two-Way In-Phase Power Divider 10-2000 MHz

Features

- Space Qualified version of DS-313
- Designed to meet the Stringent Reliability Standards of Space Hardware
- 50 Ohms Nominal Impedance
- 28 dB Midband Isolation
- 1.2:1 Midband VSWR

Description

M/A-COM's PD10-0042-S is a Two-Way In-Phase Power Divider designed to operate between 10 and 2000 MHz.

Absolute Maximum Ratings¹

Parameter	Absolute Maximum
Max. Input Power	250 milliWatt Max.
Operating Temperature	-30°C to +85°C
Storage Temperature	-65°C to +125°C


1. Operation of this device above any one of these parameters may cause permanent damage.

Electrical Specifications, T_A = +25°C

Parameter	Frequency	Units	Min.	Max.
Insertion Loss	10-1000 MHz	dB	-	1.1
	1001-1500 MHz	dB	-	1.3
	1501-2000 MHz	dB	-	-1.8
Isolation	20-1000 MHz	dB	23	-
	10-1500 MHz	dB	18	-
	1501-2000 MHz	dB	12	-
Amplitude Balance	20-1000 MHz	dB	-	.3
	10-1500 MHz	dB	-	.4
	1500-2000 MHz	dB	-	.6
Phase Balance	20-1000 MHz	-	-	4°
	10-1500 MHz	-	-	6°
	1500-2000 MHz	-	-	8°
VSWR	20-1000 MHz	-	-	1.5:1
	10-1500 MHz	-	-	1.6:1
	1501-2000 MHz	-	-	1.8:1

1. All specifications apply with a 50-Ohm source and load impedance.

FP-2



Dimensions in () are in mm.
Unless Otherwise Noted: .xxx = ±0.010 (.xx = ±0.25)
.xx = ±0.02 (.x = ±0.5)
WEIGHT (APPROX.): 0.09 OUNCES 2.5 GRAMS

Specifications subject to change without notice.

■ North America: Tel. (800) 366-2266, Fax (800) 618-8883
■ Asia/Pacific: Tel.+81-44-844-8296, Fax +81-44-844-8298
■ Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

Visit www.macom.com for additional data sheets and product information.

tyco Electronics

M/A-COM

V 2.0

1