

# Coaxial Matching Pad

50/75Ω

DC to 2000 MHz

## BMP-5075R+ BMP-5075R



### Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Input Power	0.25W

### Features

- excellent VSWR 1.15: typ.
- excellent flatness
- wideband coverage, DC to 2000 MHz

### Applications


- impedance matching

CASE STYLE: FF55

Connectors	Model	Price	Qty.
75ΩM-BNC	BMP-5075R(+)	\$24.95 ea.	(1-9)
50ΩF-BNC			

**+ RoHS compliant in accordance with EU Directive (2002/95/EC)**


The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.



### Outline Dimensions (inch/mm)

B	D	wt
.54	2.59	grams
13.72	65.79	40.0

### Electrical Schematic



### Electrical Specifications

FREQ. (MHz)	ATTENUATION (dB) Flatness Max.				VSWR (:1) Max.			POWER (W)
	Nom.	DC-100 MHz	100-1000 MHz	1000-2000 MHz	DC-100 MHz	100-1000 MHz	1000-2000 MHz	
$f_L-f_U$								
DC-2000	5.7±0.1	0.2	0.3	0.4	1.06	1.22	1.4	0.25

### Typical Performance Data

Frequency (MHz)	Attenuation (dB)	VSWR (:1)	
		50 Ω	75 Ω
10.00	5.71	1.01	1.00
20.00	5.71	1.01	1.00
60.00	5.71	1.01	1.00
100.00	5.72	1.01	1.00
110.00	5.71	1.01	1.01
555.00	5.71	1.13	1.04
1000.00	5.74	1.07	1.12
1010.00	5.74	1.07	1.12
1505.00	5.74	1.03	1.09
2000.00	5.61	1.04	1.25

