

Dual low capacitance TRANSIL™ array for ESD protection

Main product applications

Where transient overvoltage protection in ESD sensitive equipment is required, such as:

- Computers
- Printers
- Communication systems
- Cellular phone handsets and accessories
- Video equipment

Features

- 2 unidirectional low capacitance TRANSIL diodes
- Breakdown Voltage $V_{BR} = 6.1 \text{ V min}$
- Low diode capacitance (11 pF typ at 0 V)
- Low leakage current $< 0.5 \mu\text{A}$
- Very small PCB area: 0.6 mm^2
- RoHS compliant

Description


The ESDALC6V1M3 is a monolithic array designed to protect 1 line or 2 lines against ESD transients.

The device is ideal for applications where both reduced line capacitance and board space saving are required.


Benefits

- High ESD protection level
- High integration
- Suitable for high density boards

TRANSIL is a trademark of STMicroelectronics



Configuration



Order code

Part number	Marking
ESDALC6V1M3	K

Complies with the following standards

IEC61000-4-2 level 4:

15 kV (air discharge)
8 kV (contact discharge)

MIL STD 883E-Method 3015-7: class 3

HBM (Human Body Model)

1 Characteristics


Table 1. Absolute ratings ($T_{AMB} = 25^{\circ} C$ - limiting values)

Symbol		Parameter	Value	Unit
V_{PP}	ESD discharge	IEC61000-4-2 air discharge IEC61000-4-2 contact discharge	± 15 ± 8	kV
P_{PP}	Peak pulse power dissipation (8/20 μs) ⁽¹⁾	T_j initial = T_{AMB}	30	W
I_{pp}	Repetitive peak pulse current (8/20 μs)		3	A
T_j	Junction temperature		125	$^{\circ} C$
T_{stg}	Storage temperature range		-55 + 150	$^{\circ} C$
T_L	Maximum lead temperature for soldering during 10 s		260	$^{\circ} C$
T_{OP}	Operating temperature range		-40 + 125	$^{\circ} C$

1. For a surge greater than the maximum values, the diode will fail in short-circuit.

Table 2. Electrical characteristics ($T_{AMB} = 25^{\circ} C$)

Symbol	Parameter
V_{RM}	Stand-off voltage
V_{BR}	Breakdown voltage
V_{CL}	Clamping voltage
I_{RM}	Leakage current @ V_{RM}
I_{PP}	Peak pulse current
αT	Voltage temperature coefficient
V_F	Forward voltage drop



Parameter	Test condition	Min	Typ	Max	Unit
V_{BR}	$I_R = 1 \text{ mA}$	6.1		7.2	V
I_{RM}	$V_{RM} = 5 \text{ V}$			0.5	μA
R_d			1.1		Ω
αT	$I_R = 1 \text{ mA}$			4.2	$10^{-4}/^{\circ}C$
C	$V_R = 0 \text{ V}$, $F = 1 \text{ MHz}$, $V_{OSC} = 30 \text{ mV}$		11		pF

Figure 1. S21 attenuation measurement results of each channel




Figure 2. Analog crosstalk measurements between channels




Figure 3. ESD response to IEC61000-4-2 (+15 kV air discharge) on each channel




Figure 4. ESD response to IEC61000-4-2 (-15 kV air discharge) on each channel.




Figure 5. Relative variation of peak pulse power versus initial junction temperature




Figure 6. Peak pulse power versus exponential pulse duration




Figure 7. Clamping voltage versus peak pulse current (typical values)




Figure 8. Forward voltage drop versus peak forward current (typical values)




Figure 9. Junction capacitance versus reverse voltage applied (typical values)






Figure 10. Relative variation of leakage current versus junction temperature (typical values)



2 Ordering information scheme



3 Package information

Table 3. SOT883 Dimensions

Ref.	Dimensions					
	Millimetres			Inches		
	Min	Typ	Max	Min	Typ	Max
A	0.45		0.52	0.18		0.2
A1	0.00		0.05	0.00		0.02
b	0.10	0.15	0.20	0.04	0.06	0.08
b1	0.45	0.50	0.55	0.18	0.20	0.22
D		0.60			0.24	
E		1.00			0.39	
e		0.35			0.14	
e1		0.65			0.26	
L	0.20	0.25	0.30	0.08	0.10	0.12
L1	0.20	0.25	0.30	0.08	0.10	0.12

Figure 11. Footprint




Figure 12. Marking




Figure 13. ST Ecopack® recommended soldering reflow profile for PCB mounting





Figure 14. Packing information



In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com.

4 Ordering information

Part number	Marking	Package	Weight	Bulk qty	Delivery mode
ESDALC6V1M3	K	SOT883	0.96 mg	30 000	Tape and reel

5 Revision history

Date	Revision	Changes
04-Aug-2005	1	Initial release.
23-May-2006	2	Reformatted to current standards. Added soldering reflow profile diagram.
16-Jun-2006	3	Updated tape and reel illustration (Figure 14).

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED REPRESENTATIVE OF ST, ST PRODUCTS ARE NOT DESIGNED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS, WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2006 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com