



STPS2H100A/U


HIGH VOLTAGE POWER SCHOTTKY RECTIFIER

MAIN PRODUCT CHARACTERISTICS

$I_{F(AV)}$	2 A
V_{RRM}	100 V
T_j (max)	175 °C
V_F (max)	0.65 V

FEATURES AND BENEFITS

- NEGLIGIBLE SWITCHING LOSSES
- HIGH JUNCTION TEMPERATURE CAPABILITY
- LOW LEAKAGE CURRENT
- GOOD TRADE OFF BETWEEN LEAKAGE CURRENT AND FORWARD VOLTAGE DROP
- AVALANCHE RATED



DESCRIPTION

Schottky rectifier designed for high frequency miniature Switched Mode Power Supplies such as adaptators and on board DC/DC converters.

Packaged in SMA or SMB.

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter	Value	Unit
V_{RRM}	Repetitive peak reverse voltage	100	V
$I_{F(RMS)}$	RMS forward current	10	A
$I_{F(AV)}$	Average forward current	$T_L = 130^\circ\text{C } \delta = 0.5$ 2	A
I_{FSM}	Surge non repetitive forward current	$t_p = 10 \text{ ms sinusoidal}$ 75	A
I_{RRM}	Repetitive peak reverse current	$t_p = 2 \mu\text{s } F = 1\text{kHz square}$ 1	A
I_{RSM}	Non repetitive peak reverse current	$t_p = 100 \mu\text{s square}$ 1	A
T_{stg}	Storage temperature range	- 65 to + 175	°C
T_j	Maximum operating junction temperature	175	°C
dV/dt	Critical rate of rise of reverse voltage	10000	V/ μs

STPS2H100A/U

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th(j-l)}$	Junction to lead	SMA	30
		SMB	25

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions	Min.	Typ.	Max.	Unit	
I_R^*	Reverse leakage current	$T_j = 25^\circ\text{C}$	$V_R = V_{RRM}$		1	μA	
		$T_j = 125^\circ\text{C}$		0.4	1	mA	
V_F^{**}	Forward voltage drop	$T_j = 25^\circ\text{C}$	$I_F = 2\text{ A}$		0.79	V	
		$T_j = 125^\circ\text{C}$		0.6	0.65		
		$T_j = 25^\circ\text{C}$		$I_F = 4\text{ A}$			0.88
		$T_j = 125^\circ\text{C}$			0.69		0.74

Pulse test : * $t_p = 5\text{ ms}$, $\delta < 2\%$
 ** $t_p = 380\text{ }\mu\text{s}$, $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation :
 $P = 0.56 I_{F(AV)} + 0.045 I_F^2(RMS)$

Fig. 1: Average forward power dissipation versus average forward current.




Fig. 2: Average forward current versus ambient temperature ($\delta=0.5$).




Fig. 3: Non repetitive surge peak forward current versus overload duration (maximum values) (SMB).




Fig. 4: Non repetitive surge peak forward current versus overload duration (maximum values) (SMA).




Fig. 5: Relative variation of thermal impedance junction to ambient versus pulse duration (SMB).




Fig. 6: Relative variation of thermal impedance junction to ambient versus pulse duration (SMA).




Fig. 7: Reverse leakage current versus reverse voltage applied (typical values).





Fig. 8: Junction capacitance versus reverse voltage applied (typical values).



STPS2H100A/U

Fig. 9: Thermal resistance junction to ambient versus copper surface under each lead (Epoxy printed circuit board FR4, copper thickness: 35 μ m) (SMB).




Fig. 10: Thermal resistance junction to ambient versus copper surface under each lead (Epoxy printed circuit board FR4, copper thickness: 35 μ m) (SMA).






Fig. 11: Forward voltage drop versus forward current.



PACKAGE MECHANICAL DATA
 SMA

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.70	0.075	0.106
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.41	0.006	0.016
E	4.80	5.60	0.189	0.220
E1	3.95	4.60	0.156	0.181
D	2.25	2.95	0.089	0.116
L	0.75	1.60	0.030	0.063


FOOT PRINT (in millimeters)


STPS2H100A/U

PACKAGE MECHANICAL DATA SMB

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.096
A2	0.05	0.20	0.002	0.008
b	1.95	2.20	0.077	0.087
c	0.15	0.41	0.006	0.016
E	5.10	5.60	0.201	0.220
E1	4.05	4.60	0.159	0.181
D	3.30	3.95	0.130	0.156
L	0.75	1.60	0.030	0.063

FOOT PRINT (in millimeters)



Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STPS2H100A	S21	SMA	0.068g	5000	Tape & reel
STPS2H100U	G21	SMB	0.107g	2500	Tape & reel

- Band indicates cathode
- Epoxy meets UL94, V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1999 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia
Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>