


# 1.6x0.8mm SMD CHIP LED LAMP



# SUN LED

Email : sales@us.sunled.com  
 Web Site : www.sunled.com

XZBGK53W



Notes:


1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.1(0.004)$  unless otherwise noted.

Absolute maximum ratings ( $T_A=25^\circ\text{C}$ )		BGK (InGaN)	Unit
Reverse voltage	$V_R$	5	V
Forward current	$I_F$	25	mA
Forward current (peak) 1/10Duty cycle 0.1ms pulse width	$i_{FS}$	130	mA
Power dissipation	$P_T$	105	mW
Operating temperature	$T_A$	-40 ~ +85	°C
Storage temperature	$T_{stg}$	-40 ~ +85	





Operating Characteristics ( $T_A=25^\circ\text{C}$ )		BGK (InGaN)	Unit
Forward voltage (typ.) ( $I_F=20\text{mA}$ )	$V_F$	4.2	V
Forward voltage (max.) ( $I_F=20\text{mA}$ )	$V_F$	4.8	V
Reverse current ( $V_R=5\text{V}$ )	$I_R$	10	$\mu\text{A}$
Wavelength at peak emission ( $I_F=20\text{mA}$ )	$\lambda_{peak}$	515	nm
Wavelength at Dominate emission ( $I_F=20\text{mA}$ )	$\lambda_D$	525	nm
Spectral Line half-width ( $I_F=20\text{mA}$ )	$\Delta\lambda$	30	nm
Capacitance ( $V_F=0\text{V}$ , $f=1\text{MHz}$ )	$C$	45	pF

Part Number	Emitting Color	Emitting Material	Lens-color	Luminous Intensity ( $I_F=20\text{mA}$ ) med		Wavelength nm $\lambda_P$	Viewing Angle $2\theta_{1/2}$
				min.	typ.		
XZBGK53W	Green	InGaN	Water Clear	36	95	515	120°

**XZBGK53W**




◆BGK




# XZBGK53W


## ❖SMT Reflow Soldering Instructions



## ❖Recommended Soldering Pattern (Units: mm ; Tolerance: ± 0.1)



## ❖Tape Specification (Units : mm)



PACKAGE : 2000PCS / REEL.